

PRODUCT DATA SHEET

Date: December 2019	Product Name: See Below
Product Code: See Below	<p>This data represents average results from commercial production lots. If specific test results are required, samples should be taken from current production lots.</p> <p>Grey Block is manufactured in accordance with the provision of Australian Standards AS/NZS4455.1 & AS/NZS4455.3 - for masonry units.</p> <p>Grey Masonry is manufactured with 45% basalt content.</p>
<p>Description: Grey Masonry is available in 100mm, 110mm, 150mm, 200mm & 300mm Series.</p>	
Manufactured: Maryborough, QLD	
<p>Application: Veneer Walling, Non-Load Bearing Walls, Load Bearing Walls & Retaining Walls.</p>	

TYPICAL PROPERTIES	
Dimensional Category	DW1
Characteristic Unconfined Compressive Stenght (f'uc)	> 15MPa
Durability Class	General Purpose
Liability to Efflorescence	Slight
Lime Pitting Liability	Slight
Solar Absorptance Rating	Medium

SPECIFICATIONS											
Product Code	Product Name	Dimensions			Dimensional Category	Weight (kg)	Block Per m ²	No Per Pallet	F'uc (MPa)	Durability Class	
		Length (mm)	Width (mm)	Height (mm)							
10.01	100mm Series	390	90	190	Dw1	9.39	12.5	180	>15	General Purpose	
15.01	150mm Series	390	140	190	Dw1	11.47	12.5	144	>15	General Purpose	
20.01	200mm Series	390	190	190	Dw1	11.24	12.5	108	>15	General Purpose	
30.01	300mm Series	390	290	190	Dw1	18.9	12.5	72	>15	General Purpose	

CAUTION: Silica dust may be released when working with quarry products or when concrete masonry are cut, drilled, sawed, routed, chased, sanded, broken up or ground. Where contact occurs to eyes or skin wash thoroughly immediately and if inhaled move straight to fresh air, repeated long term exposure to silica dust may lead to lung diseases. To prevent this, use suitable extractive equipment, protective clothing and gear.