

PRODUCT DATA SHEET

Date: July 2018	Product Name: See Below
Product Code: See Below	Description: Grey Masonry is available in 100mm, 110mm, 140mm, 200mm & 300mm Series and 200mm Splitface Series. All these products are suitable for non-load bearing and load bearing walls, except for 100mm Series which is only suitable for veneer walls unless used as a double cavity wall.
Manufactured: Maryborough QLD	
Application: Veneer Walling & Non-load Bearing walls	

TYPICAL PROPERTIES	
Dimensional Category	DW1
Characteristic Unconfined Compressive Strength (f'uc)	> 15MPa
Durability Class	General Purpose
Liability to Efflorescence	Slight
Lime Pitting Liability	Slight
Solar Absorptance Rating	Medium

This data represents average results from commercial production lots. If specific test results are required, samples should be taken from the current production lots. Grey masonry is manufactured in accordance with the provisions of Australian Standards AS/NZS4455.1 & AS/NZS4455.3 - for masonry units. Grey masonry is manufactured with 45% basalt content.

SPECIFICATIONS						
Product Code	Product Name	Dimensions			F'uc (MPa)	Durability Class
		Length (mm)	Width (mm)	Height (mm)		
10.01	100mm Series	390	90	190	>15	General Purpose
12.709	110mm Series	390	110	190	>15	General Purpose
15.01	140mm Series	390	140	190	>15	General Purpose
20.01	200mm Series	390	190	190	>15	General Purpose
30.01	300mm Series	390	290	190	>15	General Purpose

CAUTION: Silica dust may be released when working with quarry products or when concrete masonry are cut, drilled, sawed, chased, sanded, broken up or grounded. Where contact occurs to eyes or skin wash thoroughly immediately and if inhaled move straight to fresh air, repeated long term exposures to silica dust may lead to lung diseases. To prevent this, use suitable extractive equipment, protective clothing and gear.